

# ROLLER'S **Centro S3**



**Universal, powerful, robust, handy diamond core drilling machine for core drilling for example in concrete, steel-reinforced concrete up to Ø 152 (200) mm, in masonry of all kinds, natural stone, asphalt, screed of all kinds, up to Ø 250 mm. For dry or wet drilling, hand held or with drill stand.**

- Only one universal, robust, handy diamond core drilling machine for 4 applications! **Hand held dry drilling, hand held wet drilling, dry drilling with drill stand, wet drilling with drill stand.** Ideal for applications in gas and sanitary installation, heating installation, electrical installation etc. For pipe and cable breakthroughs, air ducts, test core drilling etc.
- Powerful drive unit for vibration-free core drilling for fast, easy work. Universal for holding drilling crowns with UNC 1 ¼" female or G ½" male connection thread. With water supply device for wet drilling, with adjustable shut-off valve, quick coupling with water stop and ½" hose connection Suction rotor for sucking off dust for dry drilling with connection for conventional vacuum cleaner (accessory).
- Compact design, comfortable weight, drive unit only 7.4 kg.
- Practical spade handle in connection with stabiliser for hand held drilling. Clamping throat Ø 60 mm for holding the drive unit in ROLLER'S drill stand S2, ROLLER'S drill stand T and in suitable drill stands of other makes.
- Strong, maintenance-free, 3-step gear for optimum selection of the load speed according to the drill diameter. Blocking protection by safety slip clutch. Load speed of the drill spindle 530 rpm, 1,280 rpm, 1,780 rpm.
- Robust, powerful universal motor 2200 W, with multifunctional electronics with startup current limiting for soft startup, automatic idle speed limiting, overload protection and blocking protection. Touch switch with lock. Connecting cable with integrated personal protection switch (PRCD).
- Universal diamond core drilling crowns, universally applicable for dry and wet drilling, hand held or with drill stands. Uniform UNC 1 ¼" female connecting thread, useful length 420 mm. Optional ROLLER'S universal diamond core drilling crowns, inductively soldered, resolderable or ROLLER'S universal diamond core drilling crowns LS, laser-welded, high temperature resistant, see page 126–127. Adapter for holding in drive units with other core drilling crown connection (accessory). Easy loosening ring, for easy loosening of the drilling crown (accessory).
- **Dust extraction according to EN 60335-2-69** suction rotor for dry drilling with connection for ROLLER'S Protector and other suitable dust extractors (accessory). ROLLER'S Protector L / M safety extractor, see page 119.
- Water extractor for wet drilling up to Ø 170 mm, with connection for ROLLER'S Protector or other suitable dust extractors (accessory).
- ROLLER'S drill stands S2 or ROLLER'S drill stands T, see page 124.

Scope of Delivery

Art.-No.

## **ROLLER'S Centro S3 Basic-Pack**

Drive unit with 3-step gear, multifunctional electronics, personal protection switch PRCD, water supply device with shutoff valve, quick coupling for hose connection ½", stabiliser, single open ended wrench size 32. In steel case

180011

## **ROLLER'S Centro S3 Set T**

ROLLER'S Centro SR Basic-Pack, ROLLER'S drill stand T with set of allen keys and fastening kit for masonry and concrete

180029

## **ROLLER'S Centro S3 Set 62-82-132 T**

ROLLER'S Centro SR Basic-Pack with universal diamond core drilling crowns ROLLER'S UDKB 62, 82, 132 mm, ROLLER'S drill stand T with set of allen keys and fastening kit for masonry and concrete

180028

## **Accessories**

**ROLLER'S Centro S3 drive unit**

180001

**ROLLER'S universal diamond core drilling crowns** inductively soldered, resolderable

See page 126

**ROLLER'S universal diamond core drilling crowns LS** laser-welded, high temperature resistant

See page 127

**ROLLER'S drill stands**

See page 124

**ROLLER'S Protector L/M, wet and dry extractors**

See page 119

**Other accessories**

See page 125

**Steel case with inlay**

180600

