

# ROLLER'S Centro

## S1 / SR / S3 / S2/3.5

Accessory for ROLLER'S Centro S1, Centro SR, Centro S3, Centro S2 / 3.5 and other makes.

Art.-No.



<b>Drilling template drill stand T</b> for easy setting of the fastening holes	183605
<b>Laser drilling centre pointer</b>	183604
<b>Carbide masonry drills Ø 15 mm SDS-plus</b> for hammer anchors M12	079018
<b>Hammer anchor M12 (concrete), 50 pieces</b>	079005
<b>Setting iron</b> for hammer anchor M 12	182050
<b>Carbide masonry drills Ø 20 mm SDS-plus</b> for splaying anchors M12	079019
<b>Splaying anchor M12, pack of 10, for masonry, reusable</b>	079006
<b>Quick clamping set 160</b> for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.	079010
<b>Quick clamping set 500</b> for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers	183607
<b>Vacuum fastening drill stand T</b> , consisting of sealing ring and cover plate with hose connection	183603
<b>Vacuum pump</b> , for vacuum ≤ - 900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m <sup>3</sup> /h, condenser motor 230 V, 50–60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling	183670
<b>Drill aid G ½" with drill Ø 8 mm</b>	180150
<b>Carbide masonry drill Ø 8 mm</b> for drill aid	079013
<b>Pressurised water tank</b> for 8 l of water, for wet drilling without water connection	182006
<b>Water extractor</b> for wet drilling up to Ø 170 mm, consisting of water collection ring with sealing ring, rubber washer Ø 200 mm and universal pressure pad for all ROLLER'S drilling stands.	183606
<b>Rubber disc, Ø 200 mm, pack of 10,</b> for water extractor	183675
<b>Suction rotor for sucking off dust</b> with G ½ male thread, UNC 1¼ male thread and with connection for ROLLER'S Protector and other suitable extractors	180160
<b>Magnetic levelling block</b> with 3 spirit levels for aligning the drill stand in 3 directions	182009
<b>Drilling crown extension 200 mm</b>	180155
<b>Easy loosening ring</b> for easy loosening of the diamond core drilling crown	180015
<b>Sharpening stone</b> for diamond core drilling crowns	079012
<b>Single open ended wrench SW 41</b> for loosening of the drilling crown	079003
<b>ROLLER'S Protector L / M</b> Dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69.	See page 119