

## ROLLER'S *Filou Cu/INOX*



German Top Quality



**Powerful, compact, robust pipe circular saw especially for stainless steel tubes and copper tubes of the pressfitting systems, up to Ø 76 mm.**

- Ideal for low-burr, right-angled and fast sawing of stainless steel tubes and copper tubes of the pressfitting systems, e. g. Ø 22 mm in only 4 s.
- Adapted to the requirements of the pressfitting systems:
  - **Dry sawing**, therefore no damage to the O-ring by lubricants.
  - **Low-burr sawing** by double vice.
  - **Optimum cutting speed** damage to the pipe material by overheating.
- Stable, smooth action universal double vice with only one clamping spindle for fast, easy clamping. Both material ends remain firmly clamped during sawing. Secure clamping also of thin-walled pipes by vertically inclined low tension jaw.
- Fast, easy and quiet sawing by favourable lever effect and ideal speed (60 rpm).
- Low weight, easily portable, only 17 kg. For workbench or subframe (accessory).
- Robust, maintenance-free gear with high efficiency.
- Proven, powerful 1~ universal motor 230 V, 50–60 Hz, 500 W, with safety switch.
- Fine-toothed, hardened, specially ground ROLLER'S metal circular saw blades HSS or HSS-E (cobalt alloyed), 225 × 2 × 32, 220 teeth (accessory) for easy, accurate sawing and long life.
- Connection for fitting the ROLLER'S Rondo 10–54 E pipe deburrer.

Scope of Delivery

Art.-No.

### ROLLER'S *Filou Cu/INOX*

Saw with universal double vice, ring spanner, allen key, without saw blade

849006

Accessories

**ROLLER'S metal circular saw blade HSS**  
225 × 2 × 32, 220 teeth, especially for stainless steel pipe 849703

**ROLLER'S metal circular saw blades HSS-E**  
(cobalt alloyed) 225 × 2 × 32, 220 teeth, especially for stainless steel pipe, for very long life 849706

**Subframe** 849315

**ROLLER'S Rondo 10–54 E**  
universal outer/inner pipe deburrer Ø 10–54 mm See page 97

## ROLLER'S *Filou K*



German Top Quality



**Universel, powerful, compact, robust pipe circular saw**

↖	○	□	▭	└	●	■	■	
90°	⊕	78	55	70 × 50	50 × 50	40	40	50 × 30
45°	⊘	60	55	60 × 40	50 × 50	40	40	50 × 30

- With automatic cooling lubricant device for universal sawing.
- Fast, easy sawing by favourable lever effect and ideal speed (115 rpm).
- Low weight, easily portable, only 22 kg. For workbench or subframe (accessory).
- Easy, secure clamping of many different materials by wide, stable universal vice. Clamping insert for thin-walled pipes.
- Easy setting of the mitre angle up to 45°, without tools.
- Adjustable length stop for series production.
- Robust, maintenance-free gear with high efficiency.
- Proven, powerful 1~ universal motor 230 V, 50–60 Hz, 1200 W, with safety switch.
- Hardened, specially ground ROLLER'S metal circular saw blades HSS or HSS-E (accessory) for easy, accurate sawing and long life.

Scope of Delivery

Art.-No.

### ROLLER'S *Filou K*

Saw with automatic cooling lubricant device, universal vice, clamping insert for thin-walled pipes, ring spanner, allen key without saw blade

849007

Accessories

**ROLLER'S metal circular saw blade HSS**  
225 × 2 × 32, 120 teeth, for universal application 849700

**Cooling lubricants** See page 18

**Subframe** 849315

**Electronic speed limiter**  
for sawing stainless steel tubes 565051