

ROLLER'S Pulsar



German Top Quality



Compact, powerful electric soft soldering device for copper tubes Ø 6–54 mm.

- Electric soldering without flame, no fire risk.
- Compact, handy, easy to transport.
- Large working radius by extra long soldering tongs cable (4 m).
- Universally applicable. With rod electrodes (accessory) also in confined spaces.
- Short soldering time by high heating power (900°C) and high soldering power (2000 W!).
- Immediately ready for soldering, no heating up time, no setting.
- Trouble-free working by temperature-independent control of the solder current with protective low voltage 24 V (safety transformer). No complicated setting of pneumatic controls.
- Easy changing of the electrodes. Stainless steel electrode holders and screws.

Scope of Delivery

Art.-No.

ROLLER'S Pulsar

Electric soft soldering device with soldering tongs, 4 m long soldering tongs cables, 2 prism electrodes 164011

ROLLER'S Pulsar Super-Pack

Electric soft soldering device with soldering tongs, 4 m long soldering tongs cables, 4 prism electrodes, 2 rod electrodes, ROLLER'S Corso Cu/INOX 3–35 pipe cutter, ROLLER'S Cloth cleaning cloth, in steel case 164050

Accessories

Prism electrode, pack of 2	164111
Prism electrode with holder, pack of 2	164110
Rod electrode, pack of 2	164115
Steel case with inlay	164250
ROLLER'S Vlies (pack of 10)	160300

ROLLER'S Jet-Fire



Compact, robust propane blow torch for soft soldering of copper tubes up to Ø 35 mm.

- Self-igniting by piezo ignition, therefore lower gas consumption (only 160 g/h at full soldering power) and high work safety.
- Universal burner pipe with turbo-twist amplifier, flame temperature 1,950°C, for fast soft soldering.
- Handy, one-handed operation. No setting, no regulation.
- Locking knob for continuous operation.

Scope of Delivery

Art.-No.

ROLLER'S Jet-Fire

Propane blow torch with piezo ignition, gas connection G 3/8" LH, tube and union nut G 3/8" LH 160010

Accessories

High pressure hose 3.0 m, G 3/8" LH	152106
Pressure reducer for 5 or 11 kg gas bottles (2 bar)	152109
ROLLER'S Vlies (pack of 10)	160300

ROLLER'S Comet



Compact, robust acetylene blow torch for hard and soft soldering of copper tubes and others, up to Ø 64 mm.

- Self-igniting by piezo ignition, therefore low gas consumption and high work safety.
- Universal burner pipe with turbo-twist amplifier, flame temperature 2,500 °C for fast hard soldering.
- Only with acetylene, non additional oxygen bottle necessary.

Scope of Delivery

Art.-No.

ROLLER'S Comet

Acetylene blow torch with piezo ignition, gas connection G 3/8" LH, tube and union nut G 3/8" LH 161010